

VYBO Electric a.s.



Data Sheet

No.

Three Phase Induction Motor

Drawing No.

Customer	
Client reference	
Type	1AL-132M-4 7,5KW 400/690V 50HZ
Brand	VYBO Electric

Identification

Type:	1AL-132M-4		Frame:	132		mm
Power:	7,5	kW	Poles:	4		P
Rated Current:	380 V	15,6	Rated Voltage:	400	/	690 V
	400 V	14,8		Connection:	Δ/Y	
	415 V	14,2			Insulation Class:	F
Speed:	1450	rpm	Temperature Rise:			
Frequency:	50	Hz	Service Factor:	1,0		
Direct on line starting torque ratio (LRT/RLT):	2,3		Duty:	S1, S2, S3, S4-S9		
Direct on line pull out torque ratio (BDT/RLT):	2,3		Ambient Temperature:	-35 ~ 50°C (On request possible 62°C)		
Direct on line starting current ratio (LRA/RLA):	7		Altitude:	1000m		
Efficiency:	87	%	Protection Degree:	IP55		
Power factor:	0,84		Cooling:	IC411		
Noise level:	71	dB(A)	Mounting:	IM B (On request)		
Weight:	55	kg	Vibration:	2.8 mm/s		
Rotor inertia:	0,0296	kg/m ²	Direction of Rotation:	Both		
			Starting Method:	DOL or VFD		
			Coupling:	DIRECT		
			Load Type:	Parabolic or linear curve		
			Terminal box:	2-M32X1.5		



Bearing Information

	DE	NDE
Bearing:	63082Z	63082Z
Regreasing int.(h):		
Grease amount(g):		
Grease:		

Notes / Accessories

Deviation Sheet

	VYBO Electric	Customer

Standards

Specification:	IEC60034-1 / GB755
Test:	IEC60034-2 / GB/T1032
Noise:	IEC60034-9 / GB10069.3
Vibration:	IEC60034-14 / GB10068

Edition

Performed	Checked	Date

Item	Changes	Performed	Checked	Date